

Products : 365CleanBot-C2



Accurate Obstacle Recognition and Automatic Avoidance

2D single line laser + structured light camera + ultrasound, multi anti-collision and anti-dropping designs ensure robot accurate identification of surroundings and reliable and safe operation.





Automatic Elevator Riding

Installed Fad Odevator Gystem, Be robot can automatically take elevator, achieving multi-floors, cross area cleaning.

Autonomous Return for Charging

Low battery auto return to charging pile, after fully charged, the robot will back to where it stopped and resumed cleaning. No human intervention, non-repeated, highly increase the cleaning efficiency and quality.





Modular Design

Forward pull-type clean water tank, quick clean water refilling; Sewage water tank inside the top cover, easy pullout to discharge sewage water and garbage; Clip-type battery design, simple replacement when out of power; Drawer type cleaning module, easy cleaning and maintenance.


Applicable Ground



Marble




Tile



Terrazzo



Carpet



Marble



Tile



1	—	
	ler	razzo

Specifications : 365CleanBot-C2



Specifications of CleanBot		
Product Size	503mm x 503mm x 629mm	
Weight	42kg	
Working Weight	52kg (filled with water)	
Speed	0 ~ 0.8 m/s	
Slope Angle	9°	
Tank Capacity	Cleaning Water : 10L ; Sewage : 10L	
Network Supports	4G (Support TDD-LTE, FDD-LTE), WIFI (Support 2.4G/5G)	
Battery	Lithium Iron Phosphate, 36Ah 24V	
Battery Life	Scrubbing & Vacuuming : 6 H / Mopping : 12 H	
Charging Mode	Automatic Charging	
Charging Time	2 - 3 Hours	
Cleaning Mode	Scrubbing, Vacuuming & Mopping	
Cleaning Efficiency	800m²/h	
Cleaning Width	440mm	
Noise	<65db	
Quick-detach Design	Roller Brush, Battery, Cleaning Water Tank and Sewage Tank	
Specifications of Charging Pile		
Charging Pile Size	302mm x 90mm x 312mm	
Maximum Power	292W	
Rated Input	100 V AC to 240 V AC, 50/60 Hz, 5 A Max.	





Please contact us for more information.

SINGAPORE

MALAYSIA